



Built to last

Sturdy industrial-strength designed for continuous high-traffic operation.

MAX ADAPTER

State-of-the-art Cellular Modem at a breakthrough price point



Portable

The light and sleek enclosure offers portability in the palm of your hands.



Stay Connected

With two SIM slots and an eSIM, the MAX Adapter always has a way to connect.

Instant Unbreakable VPN

Compatible with SpeedFusion Cloud, enabling an unbreakable VPN to be built to any SpeedFusion-enabled device.

Compatible with 5G

MAX Adapter now offers a 5G compatible device option. Bringing 5G connectivity to your devices.



Connect with



Peplink Products

Protect and reinforce products with a USB port and make it a 5G/LTE WAN.

 [Learn More](#)

OR

Windows & Linux* Devices

Providing 5G/LTE connectivity for Windows and Linux devices on-the-go.



* For users on the Linux, please refer to our MAX Adapter user manual to set up.



Specifications

Cellular WAN Interfaces	Single 5G Modem	Weight	120g
Redundant SIM Slot	Yes	Operating Temperature	32° – 104°F / 0° – 40°C
Downlink/Uplink Datarate	5G: 4 Gbps / 700 Mbps LTE CAT-20: 2 Gbps / 150 Mbps	Humidity	15% – 95% (non-condensing)
Antenna Connectors	4x SMA Cellular	Warranty	1-Year Limited Warranty
Power Input	5V USB-C	Certifications	FCC, CE, IC
Power Consumption	5W (nominal), 10W (max.)	Package Content	MAX Adapter, 4x 2dBi Cellular Antennas, USB-C power cable
Dimensions	3.9 x 2.8 x 0.6 inches / 100 x 71 x 15 mm		

Ordering information

Product Code	Carrier / Category	5G Bands	LTE Bands
MAX-ADP-5GH-T	Global / 5G	5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79 5G (SA) Sub 6Ghz: n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71



Specifications

Cellular WAN Interfaces	Single LTE Modem	Weight	120g
Redundant SIM Slot	Yes	Operating Temperature	32° – 104°F / 0° – 40°C
Downlink/Uplink Datarate	CAT-12: 600 Mbps / 150 Mbps CAT-6: 300Mbps / 50Mbps	Humidity	15% – 95% (non-condensing)
Antenna Connectors	2x SMA Cellular, 1x SMA GPS	Warranty	1-Year Limited Warranty
Power Input	5V USB-C	Certifications	FCC, CE, IC
Power Consumption	5W (nominal), 10W (max.)	Package Content	MAX Adapter, 2x 2dBi 4G LTE Antennas, USB-C power cable
Dimensions	3.9 x 2.8 x 0.6 inches / 100 x 71 x 15 mm	US Carrier Certifications	Verizon, AT&T

Ordering information

Product Code	Carrier / Category	LTE Bands	3G Bands
MAX-ADP-LTEA-K-T	Worldwide CAT-12	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B18, B19, B20, B26, B28, B29, B30, B32, B41, B42, B43, B46, B48, B66	HSPA+: B1, B2, B4, B5, B6, B8, B9, B19
MAX-ADP-LTEA-W-T	Worldwide CAT-6	B1, B2, B3, B4, B5, B7, B8, B12, B13, B20, B25, B26, B29, B30, B41	WCDMA/HSPA+/DC-HSPA+: B1, B2, B3, B4, B5, B8

Accessories

Product Code	Description
ACW-232	GPS Antenna