



Case Durable **Price** Unbeatable



The AP One Rugged is made for times where you need Wi-Fi in **extreme environments**.

Its tough exterior allows for smooth operation in -40°F/-40°C to 149°F/65°C environments.



IGN I/P

Power the device normally through **Power over Ethernet** for less cable management, or an industrial **microfit connector** for a secure and durable power option.

It's **resistant to shock**, **vibrations** and **electromagnetic waves** with the certifications to prove it.

The DIN rail mount system allows for flexible deployment, no matter if it's on a wall, on a pole or on the ceiling.

Pepiink

Vi-F

Take full control of your network

This isn't just your everyday access point. With **Wi-Fi mesh** support, you can eliminate blindspots in your network, and easily control all your devices with InControl 2.

peplink

Ethernet available whenever you need it

It's not just limited to simply providing Wi-Fi either. Boost your devices with wired connections through its 3 GE ports. Having options gives you the power to deploy however you want.

AP One Rugged



1x Ethernet Port with 802.3at PoE Input 2x RP-SMA Wi-Fi Antenna Connectors I/O IGN I/P Status E. Wi-Fi DCI 3 ÷ ÷ 802.3at PoE IN peplini Power Port 2x Ethernet Ports

Specifications

Ethernet Port	3x 10/100/1000M Ethernet	Feature	GPIO ¹
Wi-Fi Standard	Simultaneous Dual-Band (2.4GHz / 5GHz) Wi-Fi 5 2X2 MIMO	Certifications ²	FCC, CE, IC, E-Mark, Railway Certification: EN 50155, Railway Certification: EN 50121-3-2,
Data Rates	2.4 GHz: up to 300Mbps 5 GHz: up to 866Mbps		Railway Certification: EN 50121-4, Vibration & Shock: EN 61373
Channel Width	20/40/80 MHz	Warranty	1-Year Limited Warranty
Recommended Concur- rent Users per Radio	60	Network	Bridge Mode Router (NAT) Mode Mesh
SSID	16		Wireless Distribution System (WDS) Support for PPPoE, Static IP, DHCP
Transmit Power	2.4GHz: 17dBm 5GHz: 17dBm		Management VLAN Spanning Tree Protocol
Antenna	External Omni Directional Antennas 2x 3dBi - 2.4GHz 2x 3dBi - 5GHz	Radio	Multiple SSID Auto Channel Selection Transmit Power Adjustment Neighbor AP Detection
Connector type	2x RP-SMA Wi-Fi Antenna connectors	AP Security	Open
Power Input	10V - 30V DC 802.3at PoE		WPA/WPA2/WPA3-Personal WPA/WPA2-Enterprise
Power Consumption	13w (max.)	Device Management	Web Administrative Interface InControl Cloud Management
Enclosure	Ruggedized Metal		Peplink AP Controller SNMP v1, v2c and v3
Dimension	4.8 x 4.2 x 1.4 inches / 122.1 x 107 x 35 mn	1	
Weight	0.8 pounds / 365 grams		
Operating Temperature	-40°- 149° F / -40°- 65° C		
Humidity	15% – 95% (non-condensing)		

¹ Available in future firmware ² Certification pending. Specifications are subject to change without notice.

AP One Rugged



Specifications

Client Management

Per SSID VLAN with QoS (802.1p/802.1q) Bandwidth Control MAC Address Filtering Layer 2 Client Isolation Limit on Max. Number of Clients

Per Client VLAN with RADIUS VLAN with VLAN Pool Bandwidth Control Multicast Filter IGMP Snooping/Multicast Enhancement

Captive Portal by InControl

Package Contents

AP One Rugged, 1 x 12V2A Power Supply (ACW-632) 2 x Dual Band Wi-Fi Antennas (ACW-342)

Ordering Information

Product Code	Description
APO-AC-RUG	Wi-Fi 5 2x2 MIMO Access Point

Featured Add-on

Product Code	Description
SVL-413	EssentialCare (1-Year) for AP One Rugged
SVL-513	EssentialCare (2-Year) for AP One Rugged
ACW-DIN-BR1-MINI	DIN Rail Mount for BR1 Mini / AP One Rugged