



# AP Pro AX

Super Rugged and Wi-Fi 6 Ready

## Built like a Tank

A metal **IP67 enclosure** provides a solid exterior to protect not only the device, but your connection as well.





## Enterprise-Grade Roaming Speeds

Bring in an **unbreakable connection** wherever you need it. Experience the speed of an office network even while you're on the field.

## Mesh Capability

With **Wi-Fi mesh support**, have the flexibility to deploy the device wherever it's needed and eliminate all the blindspots in your network.





## Turnkey Captive Portals

Captive portals are simple to create and easy to customize. Implement a **guest network** with just a few clicks.

## Seamless Integration within Peplink's Ecosystem


Built for use in the **Peplink Ecosystem**, link up the new access point to the rest of your Peplink network for instant connectivity.



## Perfect for Demanding Deployments

Provide **Wi-Fi 6** connections to factories, construction sites or harbor sides. No matter the weather, no matter the conditions.





## Specifications

<b>Ethernet Ports</b>	1x 10/100/1000M Ethernet	<b>Power Input</b>	802.3at PoE <sup>2</sup>
<b>Wi-Fi Standard</b>	Simultaneous Dual-Band (2.4GHz/5GHz) Wi-Fi 6 2X2 MIMO	<b>Power Consumption</b>	14.5W (max.)
<b>Data Rates</b>	2.4 GHz: up to 574 Mbps 5 GHz: up to 1200 Mbps	<b>Operating Temperature</b>	-40°F - 149°F -40°C - 65°C
<b>Channel Width</b>	20/40/80 MHz	<b>Warranty</b>	1-Year Limited Warranty
<b>Recommended clients per Radio</b>	256	<b>Network</b>	Bridge Mode Router (NAT) Mode Mesh Wireless Distribution System (WDS) Support for PPPoE, Static IP, DHCP Management VLAN Spanning Tree Protocol
<b>SSID Per Radio</b>	16	<b>Radio</b>	Multiple SSID Auto Channel Selection Transmit Power Adjustment Neighbor AP Detection
<b>Transmit Power</b>	2.4GHz: 24dBm 5GHz: 25dBm	<b>AP Security</b>	Open WPA/WPA2/WPA3-Personal WPA/WPA2-Enterprise
<b>Antenna</b>	External Omni Directional Antennas <sup>1</sup> 2x 8dBi - 2.4GHz 2x 8dBi - 5GHz	<b>Device Management</b>	Web Administrative Interface InControl Cloud Management Peplink AP Controller SNMP v1, v2c and v3
<b>Connector type</b>	4x Female N-Type Wi-Fi Antenna Connectors		
<b>Enclosure</b>	Plenum-rated enclosure		
<b>Dimensions</b>	9.0 x 12.2 x 2.6 inches 230 x 310 x 66 mm		
<b>Weight</b>	4.85 pounds / 2.2 kg		

<sup>1</sup> External Omni Directional Antennas are not included in the package.

<sup>2</sup> AC/DC adapter and PoE Injector are not included.  
Specifications are subject to change without notice.

## Specifications

<b>Client Management</b>	Per SSID VLAN with QoS (802.1p/802.1q) Bandwidth Control MAC Address Filtering Layer 2 Client Isolation Limit on Max. Number of Clients  Per Client VLAN with RADIUS VLAN with VLAN Pool Bandwidth Control Multicast Filter IGMP Snooping/Multicast Enhancement	<b>Captive Portal by InControl</b>	
		<b>Package Contents</b>	AP Pro AX, Water Proof DC Power Plug for IP67 (ACW-636), 1x Waterproof Ethernet Connector Kit (ACW-112), Mounting Kit (ACW-723)

## Ordering Information

Product Code	Description
APP-AX-IP67	2 x 2 MU-MIMO Wi-Fi 6 AP, Simultaneous Dual-Band 802.11a/b/g/n/ac/ax, Industrial-grade in metallic waterproof and dust-tight IP67 outdoor enclosure.

## Featured Add-on

Product Code	Description
ACW-107	802.3af/at PoE Injector. Compatible with MAX Hotspot and AP One AX Series
ACW-825	2.4GHz & 5GHz Outdoor Wi-Fi Antenna Kit include 2x 2.4GHz and 2x 5GHz Outdoor Wi-Fi Omni Antenna (2x ACW-202 & 2x ACW-308)